

# LED Panel



## Product Features

<b>Model</b>	LED Panel	<b>Housing Material</b>	Aluminum
<b>Input Voltage</b>	180 - 264 VAC	<b>Screen Material</b>	PMMA
<b>Input Frequency</b>	50/60 Hz	<b>Insulation Class</b>	II
<b>Power Factor</b>	> 0.9	<b>IP Degree</b>	IP20
<b>CRI</b>	70 (*)	<b>Lifetime</b>	30,000 h/L70
<b>CCT</b>	5000 K (**)	<b>Warranty</b>	1 year
<b>Operating Temp.</b>	-40°C - +50°C	<b>Certifications</b>	CE-RoHs

Size (cm)		Weight (kg)	Available Powers (W)							Luminous Flux (lumen)	
			10	18	26	36	40	50	60		80
30x30x1	0303	2.0									1000 - 2000
60x30x1	0603	4.0									1800 - 4500
120x15x1	1201	4.0									1800 - 4500
60x60x1	0606	6.5									2500 - 6500
120x30x1	1203	6.5									3500 - 10500
120x60x1	1206	8.0									6000 - 7500

Luminous Efficiency: 100 - 130 lm/W  
Flux data are related to Tj=85°C and CCT=5000K

\* CRI 80 variant available on request

\*\* Available CCT: 3000 K (warm), 4000 K (neutral), 5000 K (cold); on request other variants in the range 3000 K - 6000 K