

ATEX LINEAR LED

60.200002 Product Family



Product Features

Model	Atex Linear led light	Housing/Heatsink Material	Aluminum 6063
Input Voltage	100 - 277 VAC	Lens Material	PMMA
Power Frequency	50/60 Hz	Insulation Class	II
Power Factor	> 0.95	IP Degree	IP66
CRI	> 70 (*)	Lifetime	50.000
CCT	4000-6000 K (**)	Warranty	4 years
Operating Temperature	-40°C - +55°C	Certifications	CE-RoHs-ATEX-CNEX

Modules	Power		Luminous Flux	
1	30 W	30	3,360 lumen	
1	50 W	50	7,000 lumen	
1	70 W	70	9,800 lumen	

Luminous Efficiency: 140 lm/W: Flux data are related to Tj=85°C and CCT=5000 K

* CRI 80 variant upon request

 ** Available CCT: 3000 K (warm), 4000 K (neutral), 5000 K (cold)
 Other versions between 3000K and 6000K available

Lens Type		
04	05	06

Dimension and Weight																						
Modules	Dimensions (mm)																					
1	681 x 126 x 88	<table border="1"> <thead> <tr> <th>KLE1011 Series</th> <th>Dimensions(mm)</th> <th>Net Weight(kg)</th> <th>Boxed Weight(kg)</th> <th>Shipping Volume(m³)</th> </tr> </thead> <tbody> <tr> <td>300mm models</td> <td>L=385</td> <td>2.80</td> <td>3.75</td> <td>0.014</td> </tr> <tr> <td>600mm models</td> <td>L=685</td> <td>4.50</td> <td>5.40</td> <td>0.024</td> </tr> <tr> <td>1200mm models</td> <td>L=1285</td> <td>7.80</td> <td>8.65</td> <td>0.043</td> </tr> </tbody> </table>	KLE1011 Series	Dimensions(mm)	Net Weight(kg)	Boxed Weight(kg)	Shipping Volume(m ³)	300mm models	L=385	2.80	3.75	0.014	600mm models	L=685	4.50	5.40	0.024	1200mm models	L=1285	7.80	8.65	0.043
KLE1011 Series	Dimensions(mm)		Net Weight(kg)	Boxed Weight(kg)	Shipping Volume(m ³)																	
300mm models	L=385		2.80	3.75	0.014																	
600mm models	L=685	4.50	5.40	0.024																		
1200mm models	L=1285	7.80	8.65	0.043																		
2	681 x 126 x 88																					
3	1281 x 126 x 88																					

Installation Notes
<ul style="list-style-type: none"> Cables: tripolar cable with free terminals, length: 300
<ul style="list-style-type: none"> Mounting: on pole, ceiling or wall
<ul style="list-style-type: none"> Fixing: standard “C” bracket, with slots for screw fixing. Slot diameter 10 mm, length 20 mm, interdistance 200 mm
<ul style="list-style-type: none"> Rotation: ± 30° available