

sKy.Lux Indoor

IoT SENSORS

Luminosity Sensor

sKy.LUX device detects the level of luminosity of the environment and sends it via MQTT to the server. The information is processed through the configured parameters and triggers a command to the Wi-Fi lamp to perform adjustments to reach the pre-set lighting level.



| Product Features | |
|--------------------------------|---|
| Product Code | 50.100001.011 |
| Processor | Tensilica LX6 dual core processor |
| SRAM | 520 KB |
| Wi-Fi & BLE Antenna | Integrated |
| Wi-Fi Protocol | 802.11 b/g/n/d/e/l/k/r |
| Wi-Fi Standard | FCC/CE/TELEC/KCC |
| Wi-Fi Frequency range | 2.4GHz - 2.5GHz |
| Ports | 1 x temperature control 1 x luminosity sensor control 1 x PIR control 3 x buttons control 1 x display control 1 x pressure & humidity control 4 x dimming control 1 x RGBW |
| Photoresistor | LDR GL5516 5kΩ - 0,5MΩ |
| Bluetooth Protocol | Comply with BR/EDR/BLE standard of Bluetooth v4.2 |
| Power Input | 12V |
| Power Consumption | 1W |
| Operating Temperature | -40°C ~ 85°C |
| Size and weight | 88x50x20mm - 20gr |
| Warranty | 1 year |

